

AutoVoice BR-200 6W Flush-mounted loudspeaker

BBR-GM3303EV
BBR-GM3313EV

6W Loudspeaker for flush-mounting


BBR-GM33x3EV flush-mounted loudspeakers are produced in ABS. The two sizes/versions make BBR-GM33x3EV suitable for most applications where flush-mounted speakers are required.

The speakers have a wide frequency range, designed for rendering both vocal sound and music.

BBR-GM33x3EV is supplied in white color for discreet installation in ceilings.



Cut out dimensions



176 mm (3303)
196 mm (3313)

Part number	Description
116-BBR-GM3303EV	Flush mount. speaker 6W/200mm
116-BBR-GM3313EV	Flush mount. speaker 6W/230mm

Technical specifications	
Type	White ABS flush-mounted loudspeaker
Dimensions (ØxD) mm	200 x 70 + 10 (3303) 230 x 70 + 10 (3313)
Weight with transformer	0,8 kg (3303) 0,9 kg (3313)
Max. output, nominal	8W
Impedance without transformer	8 ohm
Tapping (100V transformer)	1,5 – 3 – 6W
Effective frequency range	80 - 20000Hz (3313) 125 - 20000Hz (3303)
Sound pressure (SPL) 1w/m	89,2 dB (3303) 90,7 dB (3313)
Coverage angle at ÷ 6dB	40°(h) x 40°(v) at 4KHz (3303) 35°(h) x 35°(v) at 4KHz (3313)
SPL m/max. output	97 dB (3303) 102 dB (3313)

AUTRONICA FIRE AND SECURITY AS

Fire and Security, Trondheim, Norway Phone: +47 73 58 25 00, Fax: 73 58 25 01, e-mail: info@autronicafire.no

Oil and Gas, Stavanger, Norway Phone: +47 51 84 09 00, Fax: +47 51 84 09 99

Maritime division, Spikkestad, Norway Phone: +47 31 29 55 00, Fax: +47 31 29 55 01

Visit Autronica Fire and Security AS' website: www.autronicafire.com