



### FEATURES:

- Exceptional effective non-toxic fire extinguishing agent
- Uniquely easy to install and maintain
- Approved by EPA for SNAP listing
- Ecologically safe and environmentally friendly (O.D.P.=0, G.W.P.=0)
- Very cost efficient


### Description

DSPA aerosol generators can be used as a part of a highly effective fixed extinguishing system. A DSPA generator is non-pressurized and is installed inside a room or compartment that requires protection. After activation, an aerosol cloud is generated, which expands volumetrically, flooding the space and extinguishing the fire. The DSPA generators are mainly designed to use in normally unoccupied and unoccupied areas and are effective on class A, B, C fires.

### Application

The DSPA generator 6 has an extreme low temperature profile and is recommended for the protection of medium large compartments like cable tunnels and sensitive storage rooms.

### Specifications

Model	6
Part Number	DSPA-ART00008
Dimensions	167 x 415 mm
Total weight	12500 g
Compound weight	3500 g
Volume coverage	27 - 80 m <sup>3</sup>
Discharge time	35 sec
Activation, current	Screw-in starter, 1.3A
Operation conditions	-40°C to 54°C/ Up to 95% RH at 54°C
Colour	Standard RAL 3000, other colours upon request
Min. distance for persons(75°C) from discharge outlet	
Min. distance for combustible material(200°C) from discharge outlet	
Min. distance for construction structures(400°C) from discharge outlet	

### More information:

DSPA.nl

Postbus 6572

6503 GB Nijmegen

The Netherlands

T. +31 (0) 24 35 22 573

F. +31 (0) 24 37 87 583

E info@dspa.nl



Datasheet: DSPA GENERATOR

Serie: 6

Version: 1.2

Date: 15-10-2012